

OutdoorDisplay

SPECIFICATION Wall-mount Type

ALPHA JAPAN

2015.12



Product Type		Outdoor Display (Wall-mount Type)			
Standard Model		A325MSV	A467MSV	A469MSV	A557MSV
Touch Screen Model		A325MSI	A467MSI	A469MSI	A557MSI
Panel	Screen Size	32"	46"	46"	55"
	Active Display Area (inch/mm)	27.50 x 15.47 / 698.4 x 392.85	40.09 x 22.54 / 1018.08 x 572.67	40.09 x 22.54 / 1018.08 x 572.67	47.62 x 26.79 / 1209.6 x 680.4
	Resolution	1920 x 1080			
	Aspect Ratio	16 : 9			
	Display Colors	16.7 M			
	Brightness (cd/m ² ; typ.)	2,000	2,500	5,000	2,500
	Contrast Ratio	1,300 : 1	5,000 : 1	4,000 : 1	5,000 : 1
	Response Time (ms; GTG)	25	8	8	8
	Viewing Angle (H°/V°)	178°/178°			
	Life Time (hours)	30,000	50,000	50,000	50,000
	Backlight type	LED			
Touch Screen	Response Time (ms)	50 ~ 100			
	Interface	USB 2.0			
	Touch Intensity	Permanent (protected by glass)			
	Detection Method	PCT			
	Operating System	Windows			
Input		1x VGA (D-Sub) 1x HDMI 1x DVI 1x RS232C			
Power	Operating Voltage	100 - 120V AC, 220 - 240V AC			
	Consumption (typ.)	195 W	400 W	450 W	500 W
	Consumption per nits	0.1 W (Max)	0.16 W (Max)	0.18 W (Max)	0.16 W (Ma.)
	Heater Block	Max 850 W / Peak 1.2 KW	Max 850 W / Peak 1.2 KW	Max 850 W / Peak 1.2 KW	Max 850 W / Peak 1.2 KW
Features	Auto Cooling System	Yes			
	Auto Heating System	Yes			
	Anti-Vandal Glass	Yes			
	Anti Reflection Coating	Yes			
	Auto Brightness Sensor	Yes			
Dimension	Set (W x H x D), mm	1120 x 590 x 160	1210 x 764.4 x 180	1210 x 764.4 x 180	1403.2 x 875.2 x 180
	Set (W x H x D), mm (with wall-mount)	1120 x 590 x 210	1210 x 764.4 x 234.5	1210 x 764.4 x 234.5	1403.2 x 875.2 x 235
Weight	Set (kg)	62	87	87	20
	Set (kg); with touch	-	88	88	120
Surface	Treatment	Powder coated			
Temperature	Operation (°C)	-30 ~ 50			
	Storage (°C)	-40 ~ 60			
Humidity	Non-condensing (%)	20 ~ 80			
Approvals	Ingress Protection	IP65	IP65	IP65	IP65

※ 価格：オープン価格

※ 製品の規格及び外観は改良のため予告なく変更される場合があります。詳しくは当社営業担当までお問い合わせ下さい。